

# ToLEDo GLS

ToLEDo PRESENCE A65 1055LM 830 E27 SL

0027547



## Product features

- ToLEDo™ Presence - energy saving smart lighting solution • Turn on/off automatically when infrared signal is detected • Operating mode: – Lumen output drops to 50% when no signal is detected for 40 seconds and power consumption also reduces to 6W – Lamp go on stand-by mode when no signal is detected for 60 seconds – Power consumption on stand-by mode is 0.5W • Sensor can pick infrared signal up to maximum distance of 3 meters • 1055lm output equivalent to 75W incandescent lamp • Colour temperature – 3000K • 15,000 hours average rated life • 3 years warranty • The lamp sensor should be free of any obstruction when used in open luminaires • This lamp is not suitable for enclosed luminaires • High colour rendering – CRI80

## PRODUCT OVERVIEW

Product code	0027547
Product name	ToLEDo PRESENCE A65 1055LM 830 E27 SL
Technology	LED
Watt (Rated) (W)	12
Fixture rating	Open
General application	Hospitality, Education, Residential & Consumer,
Certifications	EUTIE103
ETIM Class	EC001959
Luminous flux (lm)	1055
Colour temperature (K)	3000
Light colour	830 Warm White
CRI (Ra)	80
Wattage (W)	12
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288275475

## DATA TABLE

### General data

Product code	0027547
Product name	ToLEDo PRESENCE A65 1055LM 830 E27 SL
Technology	LED
Watt (Rated) (W)	12
Fixture rating	Open
General application	Hospitality, Education, Residential & Consumer,
Operating Temperature Range (°C)	25
Certifications	EUTIE103
ETIM Class	EC001959

## ToLEDo GLS

*ToLEDo PRESENCE A65 1055LM 830 E27 SL***0027547**

## Optical data

<b>Luminous flux (lm)</b>	1055
<b>Luminous flux (Rated) (lm)</b>	1055
<b>Colour temperature (K)</b>	3000
<b>Light colour</b>	830 Warm White
<b>CRI (Ra)</b>	80
<b>Beam angle (Rated) (°)</b>	150

## Electrical data

<b>Wattage (W)</b>	12
<b>Starting time (max) (s)</b>	0.5
<b>Warm-up time to 60% of full light (max) (s)</b>	1
<b>Product Voltage (V)</b>	230
<b>Lamp power factor</b>	0.55
<b>No. Of switching cycles before premature failures</b>	50000
<b>Lamp Energy Label (class)</b>	A+
<b>kWh per 1000 hours burning time</b>	12
<b>Nominal Frequency (Hz)</b>	50/60Hz

## Lifetime data

<b>Average life (Nominal) (h)</b>	15000
<b>Average life (Rated) (h)</b>	15000

## Physical data

<b>Nominal Product Length (mm)</b>	125
<b>Nominal Product Diameter (mm)</b>	65
<b>Weight (kg)</b>	0.075

## Packaging

<b>Single packaging type</b>	Carton
<b>Product EAN number</b>	5410288275475
<b>Packaging single length (cm)</b>	6.5
<b>Packaging single width (cm)</b>	6.5
<b>Packaging single height (cm)</b>	13.0
<b>DUN14 (inner)</b>	25410288275479
<b>Units per inner package</b>	6
<b>Packaging inner length (cm)</b>	13.6
<b>Packaging inner width (cm)</b>	13.7
<b>Packaging inner height (cm)</b>	20.3
<b>DUN14 (outer)</b>	15410288275472

## ToLEDo GLS

ToLEDo PRESENCE A65 1055LM 830 E27 SL

**0027547**

Units per outer package	60
Packaging outer length (cm)	71.0
Packaging outer width (cm)	21.5
Packaging outer height (cm)	29.0

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes

