

Toledo Mirage T45 TOLEDO MIRAGE T45 0029917

Product features

 A perfect choice for hospitality, decorative and mood lighting applications Unique and innovative lamp design and construction Low-lumen output to create the low-lit effect and gives no glare Low power construction: only 2.5WPerfect for SylPendant fixtures - a range of unique and elegant E27 lamp pendants, available in copper, brass, black and white finish Candlelight 2000K colour temperature creates a warm and cosy ambience High colour rendering - CRI80 High quality, scratch and temperature resistant golden tinted glass envelope 25,000 hours of average rated life. Last 25 times longer than incandescent lamps Omni-directional light distribution of 300° Non-dimmable More than 100,000X switching cycles 3 years warranty



NOTES

undefined

PRODUCT OVERVIEW

| IPC Code | 0029917 |
|----------------------------|------------------------|
| Product name | TOLEDO MIRAGE T45 |
| Technology | LED |
| Watt (Rated) (W) | 2.5 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Residential & Consumer |
| Certifications | EUTIE103 |
| ETIM Class | EC001959 |
| E-number Fl | 4740681 |
| Luminous flux (Im) | 125 |
| Colour temperature (K) | 2000 |
| Light colour | Candlelight |
| CRI (Ra) | 80 |
| Wattage (W) | 2.5 |
| Product Voltage (V) | 230 |
| Average life (Nominal) (h) | 25000 |
| Product EAN number | 5410288299174 |
| | |

DATA TABLE

| General data | |
|---------------------|------------------------|
| IPC Code | 0029917 |
| Product name | TOLEDO MIRAGE T45 |
| Technology | LED |
| Watt (Rated) (W) | 2.5 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Residential & Consumer |



Toledo Mirage T45 TOLEDO MIRAGE T45 0029917

| Operating Temperature Range (°C) | 25 |
|--|---|
| Certifications | EUTIE103 |
| ETIM Class | EC001959 |
| E-number Fl | 4740681 |
| | 4740001 |
| Optical data | |
| Luminous flux (Im) | 125 |
| Luminous flux (Rated) (Im) | 125 |
| Colour temperature (K) | 2000 |
| Light colour | Candlelight |
| CRI (Ra) | 80 |
| Beam angle (Rated) (°) | 100 |
| Electrical data | |
| | |
| Wattage (W) | 2.5 |
| Starting time (max) (s) | 0.5 |
| Warm-up time to 60% of full light (max) (s) | 1 |
| Product Voltage (V) | 230 |
| Lamp power factor | 0.5 |
| No. Of switching cycles before premature | 100000 |
| failures | |
| Lamp Energy Label (class) | A+ |
| kWh per 1000 hours burning time | 3 |
| Nominal Frequency (Hz) | 50/60Hz |
| | |
| Lifetime data | |
| | 25000 |
| Average life (Nominal) (h) | 25000 |
| | 25000 25000 |
| Average life (Nominal) (h) Average life (Rated) (h) | |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data | 25000 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) | 25000 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) | 25000 150 45 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) | 25000 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) | 25000 150 45 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging | 25000 150 45 0.11 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) | 25000 150 45 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number | 25000 150 45 0.11 Carton 5410288299174 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) | 25000 150 45 0.11 Carton |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) | 25000 150 45 0.11 Carton 5410288299174 17.3 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) | 25000 150 45 0.11 Carton 5410288299174 17.3 5.4 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) | 25000 150 45 0.11 Carton 5410288299174 17.3 5.4 5.4 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package | 25000 150 45 0.11 Carton 5410288299174 17.3 5.4 5.4 5.4 15410288299171 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) | 25000 150 45 0.11 Carton 5410288299174 17.3 5.4 5.4 5.4 15410288299171 6 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) | 25000 150 45 0.11 Carton 5410288299174 17.3 5.4 5.4 5.4 5.4 15410288299171 6 18.0 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) | 25000 150 45 0.11 Carton 5410288299174 17.3 5.4 5.4 5.4 15410288299171 6 18.0 12.0 |
| Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) | 25000 150 45 0.11 Carton 5410288299174 17.3 5.4 5.4 5.4 15410288299171 6 18.0 12.0 |
| Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) | 25000 150 45 0.11 Carton 5410288299174 17.3 5.4 5.4 5.4 15410288299171 6 18.0 12.0 |



Toledo Mirage T45 TOLEDO MIRAGE T45 0029917

| Special purpose lamp | No |
|-------------------------------------|--|
| Dry applications use only | Yes |
| Suitable for household illumination | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |

