

## RefLED PAR30

## RefLED RETRO PAR30 DIM 820LM 830 36° SL 0028270

#### **Product features**

- High performance LED PAR lamps with the same look and feel of traditional PAR lamps
- Glass construction means no colours clashing between the lamp and fixture
- Reduced visible heatsink from the front
- Mercury-free solution
- · Lower maintenance cost
- Lifetime: up to 25,000 hours
- · High lumen efficacy
- Dimmable on approved dimmers\*
- 3 year warranty
- Suitable for general lighting and accent lighting for hotels, restaurants, bars, lobbies, corridors and













#### **PRODUCT OVERVIEW**

IPC Code	0028270
Product name	RefLED RETRO PAR30 DIM 820LM 830 36° SL
Technology	LED
Watt (Rated) (W)	11
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
Certifications	EUTIE105
ETIM Class	EC001959
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Wattage (W)	11
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288282701

#### **DATA TABLE**

General data	
IPC Code	0028270
Product name	RefLED RETRO PAR30 DIM 820LM 830 36° SL
Technology	LED
Watt (Rated) (W)	11
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail



# RefLED PAR30

# RefLED RETRO PAR30 DIM 820LM 830 36° SL 0028270

Operating temperature rated (°C)	25
Certifications	EUTIE105
ETIM Class	EC001959
Optical data	
Rated Luminous Flux Useful (Im)	820
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Beam angle (Rated) (°)	36
Electrical data	
Wattage (W)	11
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<0.5
Product Voltage (V)	230
Lamp power factor	0.9
No. Of switching cycles before premature failures	50000
Dimmable	Yes
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	11
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000
Physical data	
Nominal Product Length (mm)	94
Nominal Product Diameter (mm)	95
Weight (kg)	0.225
Packaging	
Single packaging type	Carton
Product EAN number	5410288282701
Packaging single length / height (cm)	11.1
Packaging single width (cm)	10.2
Packaging single depth (cm)	10.2
DUN14 (outer)	15410288282708
Units per outer package	6
Packaging outer length / height (cm)	34.8
Packaging outer width (cm)	23.7
Packaging outer depth (cm)	15.7



## RefLED PAR30 RefLED RETRO PAR30 DIM 820LM 830 36° SL 0028270

#### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	General lighting
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers

