

## RefLED R50 REFLED R50 V3 470LM 830 E14 SL 0028411



#### **Product features**

- Energy efficient LED alternative for traditional incandescent and halogen blown reflector lamp
- Modern construction and attractive design
- · Mercury free solution
- Long average rated lifetime: 15,000 hours
- · Lower maintenance cost compared to traditional lamps
- Non-dimmable
- · 3 years warranty
- Perfect for general lighting applications: residential lighting, down lights, hotels, hotels, restaurants, bars, lobbies, corridors, halls, etc









### **NOTES**

### undefined

## PRODUCT OVERVIEW

IPC Code	0028411
Product name	REFLED R50 V3 470LM 830 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE105
ETIM Class	EC001959
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Wattage (W)	5
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288284118

### **DATA TABLE**

General data	
IPC Code	0028411
Product name	REFLED R50 V3 470LM 830 E14 SL
Technology	LED



# RefLED R50 REFLED R50 V3 470LM 830 E14 SL 0028411

Mark (Dated) (M)	-
Watt (Rated) (W)	5 E14
Cap/Base	
Fixture rating	Open
General application	Hospitality,Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUTIE105
ETIM Class	EC001959
Optical data	
Rated Luminous Flux Useful (Im)	470
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Beam angle (Rated) (°)	120
Electrical data	
Wattage (W)	5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max)	2
(s)	
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Dimmable	No
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	5
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
	4-00
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Physical data	
Nominal Product Length (mm)	83
Nominal Product Diameter (mm)	50
Weight (kg)	0.035
ייש	
Packaging	
Single packaging type	Carton
Product EAN number	5410288284118
Packaging single length / height (cm)	4.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	7.8
DUN14 (outer)	15410288284115
Units per outer package	6



## RefLED R50 REFLED R50 V3 470LM 830 E14 SL 0028411

Packaging outer length / height (cm)15.8Packaging outer width (cm)10.7Packaging outer depth (cm)8.7

## Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

