SYLVANIA

ToLEDo Stick TOLEDO STICK 1150LM 840 E27 SL 0029929

Product features

 A bright, all-around lighting solution for living rooms, wall lights, ceiling lights, compact and decorative luminaires • Quick and easy replacement of 75W incandescent lamp • 15,000H average rated life - last 15X longer than incandescent/halogen lamps • 85% energy savings compared to incandescent • Last 50% longer and consume 45% less energy compared to comact flourescent integrated lamps • A+ energy rating - up to 105 lm/W • Omni-directional light distribution • Non-dimmable



PRODUCT OVERVIEW

IPC Code0029929Product nameTOLEDO STICK 1150LM 840 E27 SLTechnologyLEDWatt (Rated) (W)11Cap/BaseE27Fixture ratingOpenGeneral applicationHospitality, Residential & ConsumerCertificationsEUTIE103ETIM ClassEC001959E-number FI4740650Luminous flux (Im)1150Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80
Watt (Rated) (W)11Cap/BaseE27Fixture ratingOpenGeneral applicationHospitality, Residential & ConsumerCertificationsEUTIE103ETIM ClassEC001959E-number FI4740650Luminous flux (Im)1150Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80
Cap/BaseE27Fixture ratingOpenGeneral applicationHospitality, Residential & ConsumerCertificationsEUTIE103ETIM ClassEC001959E-number FI4740650Luminous flux (Im)1150Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80
Fixture ratingOpenGeneral applicationHospitality, Residential & ConsumerCertificationsEUTIE103ETIM ClassEC001959E-number FI4740650Luminous flux (Im)1150Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80
General applicationHospitality, Residential & ConsumerCertificationsEUTIE103ETIM ClassEC001959E-number FI4740650Luminous flux (Im)1150Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80
CertificationsEUTIE103ETIM ClassEC001959E-number FI4740650Luminous flux (Im)1150Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80
ETIM ClassEC001959E-number FI4740650Luminous flux (Im)1150Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80
E-number FI 4740650 Luminous flux (Im) 1150 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80
Luminous flux (Im)1150Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80
Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80
Light colour Cool White CRI (Ra) 80
CRI (Ra) 80
Colour Variation Initial (SDCM) 6
Colour Consistency (SDCM) 6
Beam Angle (°) 240
Wattage (W) 11
Product Voltage (V) 230
Average life (Nominal) (h) 15000
Product EAN number 5410288299297

DATA TABLE

General data	
IPC Code	0029929
Product name	TOLEDO STICK 1150LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	11
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating Temperature Range (°C)	25
Certifications	EUTIE103



ToLEDo Stick TOLEDO STICK 1150LM 840 E27 SL 0029929

ETIM Class	EC001959
E-number FI	4740650
	4740050
Optical data	
Luminous flux (Im)	1150
Luminous flux (Rated) (Im)	1150
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	80
	6
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	
Beam Angle (°)	240
Beam angle (Rated) (°)	240
Lumen maintenance at end of nominal	70
life (%)	
Electrical data	
	11
Wattage (W) Storting time (max) (a)	0.5
Starting time (max) (s)	
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	11
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Dia dia data	
Physical data	
Nominal Product Length (mm)	133
Nominal Product Diameter (mm)	45
Weight (kg)	0.07
Packaging	
Single packaging type	Carton
Product EAN number	5410288299297
Packaging single length / height (cm)	13.7
Packaging single width (cm)	4.7
Packaging single depth (cm)	4.7
DUN14 (inner)	25410288299291
Units per inner package	10
Packaging inner length / height (cm)	25.0
Packaging inner width (cm)	10.5
Packaging inner depth (cm)	15.5



ToLEDo Stick TOLEDO STICK 1150LM 840 E27 SL 0029929

DUN14 (outer)	15410288299294
Units per outer package	60
Packaging outer length / height (cm)	34.0
Packaging outer width (cm)	26.5
Packaging outer depth (cm)	34.0
Safety data	
Safety data Breakage cleaning instructions	Not applicable
	Not applicable No
Breakage cleaning instructions	••
Breakage cleaning instructions Special purpose lamp	No

