## Product datasheet



DALI MCU | Light management systems



#### Areas of application

- Conference rooms
- Restaurants
- Shop lighting

#### Product family benefits

- Intuitive manual dimming and switching
- Individual setting of minimal brightness level

#### Product family features

- Up to 4 DALI MCUs can be connected in parallel to set up multiple control points
- Automatic synchronization between the control points
- Cover and rotary switch in neutral white
- Length of the DALI control cable: up to 300 m


# Product datasheet

#### Technical data

## **Electrical data**

Nominal voltage	230 V
Mains frequency	5060 Hz
System wattage	2.00 W

#### **Dimensions & weight**



Length	80.0 mm
Width	80.0 mm
Height	50.0 mm
Product weight	98.00 g
Mounting hole spacing, length	70.0 mm

#### **Colors & materials**

#### Temperatures & operating conditions

#### Capabilities

Dimmable	Yes
Dimming interface	DALI
Number of control outputs	1
Type of installation	Integrated in flush device box

## **Certificates & standards**

Type of protection	IP20
Protection class	II

## Product datasheet

#### Logistical data

Commodity code	853650809000

Equipment / Accessories

- Suitable for up to 25 electronic control gears
- Flexible expansion via DALI repeaters or further DALI MCUs
- Cover and rotary knob included

#### Download Data

	File	
★	Declarations of conformity 340446_Declaration of Conformity_MCU	
7	Installation/Operation notice 334251_DALI MCU – digital rotary dimmer	
7	Installation guide 334686_DALI_MCU–digital_rotary_dimmer	

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321189721		Shipping carton box 15	430 mm x 149 mm x 210 mm	13.45 dm³	2190.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.