

## LIVIA 60

### DOWNLIGHT

LED ceiling surface downlight with no visible screws, suitable for outdoor and indoor installations. Made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Supplied with TÜV-CB certified, long-life, and efficient **G9 LED lamps included**. Insulation class II, protection rating IP44.

*Lampada a soffitto senza viti a vista adatta sia ad uso esterno che interno. Realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Fornita con inclusa **lampadina a LED G9**, certificata TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP44.*



LIVIA 60  
1A9.000



1A9.000.Z1L



**LIVIA 60 - COMPONENTS**

**IP55**



**BASE** made of shockproof resin material suitable for the electrical devices fixation and provided complete with G9 lampholder.

***BASE** in resina antiurto predisposta per il fissaggio degli accessori elettrici e fornita completa di portalamпада G9.*

**DIFFUSER** with frosted finishing made of shockproof resin material (PC), complete with silicone rubber gasket to ensure high protection against external agents.

***DIFFUSORE** satinato in resina antiurto (PC) completo di guarnizione in gomma silconica per garantire un alto livello di protezione contro gli agenti esterni.*

**COVER** made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Quick and easy locking system to the base without screws.

***COVER** realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Sistema di aggancio alla base facile e veloce senza l'ausilio di viti.*

**LIVIA 60**



**Dimensions and weight**

Diameter: Ø60 mm

Height: 69 mm

Weight: 0,10 Kg

**Moulded colours:**

Black   White   Grey

**Diffuser PC:**

Frosted

**G9 LED**

**100 - 240 V**

\*ADD. SUFFIX



**1,7 W**

**170 Lm**

4000 K

.Z1L

3000 K

.Z1R

Ceiling surface downlight supplied with TÜV-CB certified, long-life and efficient **G9 LED lamp included**. Quick and easy lamp replacement for a very simple maintenance after installation.

- **COST SAVING:** long-life and efficient LED light sources
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** G9 standard lamp holder
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments
- **100-240V:** wide voltage range to protect the driver from power surges.

**LED LAMPS**



Technical details on page 552.

\* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE