

LIVIA 90

DOWNLIGHT

LED ceiling surface downlight with no visible screws, suitable for outdoor and indoor installations. Made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Supplied with TÜV-CB certified, long-life, efficient and **Kelvin settable GU10 LED lamps included**. Insulation class II, protection rating IP 44.

*Lampada a soffitto senza viti a vista adatta sia ad uso esterno che interno. Realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Completa di **lampadine a LED GU10 con Kelvin impostabile**, certificate TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP44.*

LIVIA 90
2A9.000



2A9.000.L1K

CCT SETTABLE



2700 K

4000 K

SDCM <6



LIVIA 90 - COMPONENTS

IP55



BASE made of shockproof resin material suitable for the electrical devices fixation and provided complete with GU10 lampholder.

***BASE** in resina antiurto predisposta per il fissaggio degli accessori elettrici e fornita completa di portalamпада GU10.*

DIFFUSER with frosted finishing made of shockproof resin material (PC), complete with silicone rubber gasket to ensure high protection against external agents.

***DIFFUSORE** satinato in resina antiurto (PC) completo di guarnizione in gomma silconica per garantire un alto livello di protezione contro gli agenti esterni.*

COVER made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Quick and easy locking system to the base without screws.

***COVER** realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Sistema di aggancio alla base facile e veloce senza l'ausilio di viti.*

LIVIA 90

— 96 —

105

Dimensions and weight

Diameter: Ø96 mm

Height: 105 mm

Weight: 0,26 Kg

Moulded colours:

Black White Grey

Diffuser PC:

Frosted

GU10 LED

100 - 240 V

*ADD. SUFFIX



Ceiling surface downlight supplied with TÜV-CB certified, long-life and efficient **Kelvin settable GU10 LED lamp** included. Different wattages available. Quick and easy lamp replacement for a very simple maintenance after installation.

- **COST SAVING:** long-life and efficient LED light sources
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** GU10 standard lamp holder
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments
- **SUITABLE FOR OUTDOOR USE:** built-in driver fully protected against heat and humidity by silicone paste.

GU10 LED	3,5W	350 Lm	4000 K	.U1K
			2700 K	
GU10 LED	6W	600 Lm	4000 K	.L1K
			2700 K	

3.5W 350 Lm = 50W HALOGEN
SAVE 92%


6W 600 Lm = 100W HALOGEN
SAVE 95%

LED LAMPS



Technical details on page 552.

CCT SETTABLE LED LAMP



CCT switch settable in two different positions, to select the desired Kelvin temperature (2700K/4000K) and get a customized ambience.