# i-onG2SM - Expandable 50 zone control panel



The i-onG2SM is a Grade 2 control panel with 10 zones on board, expandable to 50, and feature-packed to deliver you real benefits.

Built with cyber security in its DNA the i-onG2SM is SecureConnect™ Cloud and App enabled

#### **Decimal expansion system**

Expanders have 10 zones in addition to the 10 zones on the end station. It provides 25% more zones per expander than traditional 8 zone expanders. A 30 zone radio expander is also available.

#### Performance bus

Fit up to 20 bus devices: expanders, keypads or power supplies.

#### Semi-auto addressing

Prevents address duplication for bus mounted devices, saving hours of installation diagnostic time.

#### Audible bus device tracing

Locate any bus device quickly and easily. Reduce the time taken to complete maintenance and service calls.

#### At a glance...

- Ten zones expandable to 50
- 50 user codes
- SecureConnect<sup>™</sup> enabled
- Range of keypad options
- App for end user control and notification
- Common programming across the range



## **Scantronic product datasheet**

## **Product specification**

| Feature                           | Description  |
|-----------------------------------|--|
| Compliance                        | EN50131 PD662:2017 Grade 2   |
| Zones on board                    | 10   |
| Total zone capacity               | 50   |
| Total number of buses             | 1  |
| Number of users                   | 50   |
| Number of outputs                 | 50 system plus 12 communicator   |
| Number of partitions              | 5  |
| Number of part sets per partition | 3  |
| Event log size                    | 1,500  |
| Number of bus devices             | 20   |
| Firmware update                   | SD card or Cloud   |
| Power supply                      | 1A   |
| Remote communications             | Ethernet included. Choice of plug on communicators for PSTN, GSM or 4G |
| Communications security           | SSL/TLS - when communicating with SecureConnect™ App or Cloud          |
| Battery (maximum capacity)        | 1 * 7Ah  |
| Micro sd card                     | Yes  |
| Size                              | 239mm (h) x 250mm (w) x 90mm (d).                                      |
| Weight                            | 2.8Kg - Panel without battery  |
| Temperature range                 | Environmental class 2 -10°C to 55°C 93% RH                             |

## **Compatible products**

| Product Code  | Description  |
|---------------|--|
| Keypads       |  |
| KEY-K01       | Wired keypad   |
| KEY-KP01      | Wired keypad with built-in proximity reader  |
| KEY-KPZ01     | Wired keypad with built-in proximity reader and 2 zone inputs  |
| KEY-RKPZ-KIT  | 2 way radio keypad and base station  |
| KEY-RKPZ      | 2 way radio keypad   |
| KEY-FKPZ-BK   | Flush mount keypad - piano black finish  |
| KEY-FKPZ-SC   | Flush mount keypad - satin chrome finish   |
| KEY-FKPZ-WH   | Flush mount keypad - bright white finish   |
| i-KP01        | Wired keypad with large display and built in proximity reader  |
| Expanders     |  |
| EXP-W10       | 10 zone wired expander   |
| EXP-R10       | 10 zone radio expander   |
| EXP-R30       | 30 zone radio expander   |
| EXP-PSU       | 3 Amp 10 zone intelligent powered expander in large metal housing  |
| Communicators |  |
| COM-SD-PSTN   | PSTN speech dialler and ARC communicator   |
| COM-SD-GSM    | GSM speech dialler and ARC communicator  |
| COM-DATA-4G   | 4G data communicator for connection to SecureConnect™ Cloud and data ARC communications  |
| Accessories   |  |
| MISC-SHFPK5   | Pack of 5 accessory shelves. This enables a third party communicator or expander to be mounted above the panel PCB without hindering access to the panel PCB |
| ADP-10CC      | Allows ten 4 wire zones to be used on the panels ten FSL (Fully Supervised Loop) zones   |
|               |  |











