

ToLEDo LifeStyle T180 BLACK DIMMABLE TOLEDO LIFESTYLE T180 BLK 150LM E27 SL 0029983

Product features

• New state-of-the-art designer lamps for decorative and hospitality applications• Unconventional design that looks good on both off and on. Flexible LED filament construction. Dimming functionality helps to vary lighting scene as lamps can be dimmed from 100% to 10% and reduce energy consumption• Low power - only 4W• Lumen output - 150lm• 2000K colour temperature to create an intimate atmosphere• Good colour rendering - CRI 80• 15,000 hours average rated life. Last 15 times longer than incandescent lamps. Perfectly complements Sylvania E27 SylPendant range available in brass, copper, white and black finish. Omni-directional light distribution. More than 100,000X switching cycles• 3 years warranty











PRODUCT OVERVIEW

Product name	TOLEDO LIFESTYLE T180 BLK 150LM E27 SL
Technology	LED
Watt (Rated) (W)	4
Cap/Base	E27
Fixture rating	Open
General application	Hospitality
ETIM Class	EC001959
Warranty	3 years
Luminous flux (Im)	150
Colour temperature (K)	2000
Light colour	Candlelight
CRI (Ra)	80
Wattage (W)	4
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288299839

DATA TABLE

General data	
Product name	TOLEDO LIFESTYLE T180 BLK 150LM E27 SL
Technology	LED
Watt (Rated) (W)	4
Cap/Base	E27
Fixture rating	Open
General application	Hospitality
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	3 years
Optical data	
Luminous flux (lm)	150
Luminous flux (Rated) (Im)	150



ToLEDo LifeStyle T180 BLACK DIMMABLE TOLEDO LIFESTYLE T180 BLK 150LM E27 SL 0029983

Colour temperature (V)	2000
Colour temperature (K)	2000
Light colour	Candlelight
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Wattage (W)	4
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<2.0
Product Voltage (V)	230
Lamp power factor	0.7
No. Of switching cycles before premature failures	>100000
Inrush Current (A)	1.42
Lamp Energy Label (class)	A
kWh per 1000 hours burning time	4
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	227
Max. Luminaires per 16A C Breaker	363
Max. Luminaires per 20A C Breaker	454
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Average ine (Nateu) (II)	10000
Physical data	
Nominal Product Length (mm)	173
Nominal Product Diameter (mm)	180
Weight (kg)	0.244
Packaging	
Single packaging type	
Product EAN number	Carton
I TOUGOL LAN HUHIDOI	Carton 5410288299839
Packaging single length / height (cm)	
	5410288299839
Packaging single length / height (cm)	5410288299839 20.0
Packaging single length / height (cm) Packaging single width (cm)	5410288299839 20.0 20.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	5410288299839 20.0 20.0 19.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer)	5410288299839 20.0 20.0 19.0 15410288299836
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	5410288299839 20.0 20.0 19.0 15410288299836 2
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm)	5410288299839 20.0 20.0 19.0 15410288299836 2 41.5
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm)	5410288299839 20.0 20.0 19.0 15410288299836 2 41.5 21.5
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data	5410288299839 20.0 20.0 19.0 15410288299836 2 41.5 21.5
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Breakage cleaning instructions	5410288299839 20.0 20.0 19.0 15410288299836 2 41.5 21.5 21.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Breakage cleaning instructions Special purpose lamp	5410288299839 20.0 20.0 19.0 15410288299836 2 41.5 21.5 21.0 Not applicable No
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Breakage cleaning instructions Special purpose lamp Dry applications use only	5410288299839 20.0 20.0 19.0 15410288299836 2 41.5 21.5 21.0 Not applicable No Yes
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Breakage cleaning instructions Special purpose lamp	5410288299839 20.0 20.0 19.0 15410288299836 2 41.5 21.5 21.0 Not applicable No



ToLEDo LifeStyle T180 BLACK DIMMABLE TOLEDO LIFESTYLE T180 BLK 150LM E27 SL 0029983

Safety message

Dimmable with approved dimmers

TECHNICAL DRAWINGS



