



MASTER Glass LED bulbs

MAS LEDBulb DT3.4-40W E27 927A60CL G

Featuring a classic heritage design, these filament MASTER glass bulbs combine the familiar shapes of incandescent glass LED bulbs with the benefits of long-lasting LED technology. Ideal for creating a cozy atmosphere for customers, these glass LED bulbs provide excellent quality of light. MASTER glass bulbs can be dimmed for different lumen levels and color temperatures (dimmable glass led bulbs). They also deliver significant energy savings, using 30% less energy compared to normal LED bulbs. By offering a lifetime of 25,000 hours, these dimmable glass LED bulbs also reduce maintenance costs.

Product data


General information		LLMF At End Of Nominal Lifetime (Nom) 70 %	
Cap-Base	E27 [E27]		
EU RoHS compliant	Yes		
Nominal Lifetime (Nom)	25000 h		
Switching Cycle	20000X		
Flux measurement reference	Sphere		
Tier	MASTER		
Light technical		Operating and electrical	
Color Code	922-927 [CCT of 2200K-2700K]	Input Frequency	50 to 60 Hz
Luminous Flux (Nom)	470 lm	Power (Nom)	3.4 W
Color Designation	Warm Glow(WG)	Lamp Current (Nom)	24 mA
Correlated Color Temperature (Nom)	2200 2700 K	Wattage Equivalent	40 W
Luminous Efficacy (rated) (Nom)	138 lm/W	Starting Time (Nom)	0.5 s
Color Consistency	<6	Warm Up Time to 60% Light (Nom)	0.5 s
Color Rendering Index (Nom)	90	Power Factor (Nom)	0.6
		Voltage (Nom)	220-240 V
		Temperature	
		T-Ambient (Max)	45 °C
		T-Ambient (Min)	-20 °C
		T-Case Maximum (Nom)	70 °C

MASTER Glass LED bulbs

Controls and dimming	
Dimmable	Only with specific dimmers
Mechanical and housing	
Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	A60 [A 60mm]
Approval and application	
Energy Efficiency Class	D
Energy Consumption kWh/1000 h	4 kWh
EPREL Registration Number	1109129

Product data	
Full product code	871951444967100
Order product name	MAS LEDBulb DT3.4-40W E27 927A60CL G
EAN/UPC - Product	8719514449671
Order code	929003009982
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929003009982
Net Weight (Piece)	0.030 kg


Dimensional drawing




MAS LEDBulb DT3.4-40W E27 927A60CL G

Product	D	C
MAS LEDBulb DT3.4-40W E27 927A60CL G	60 mm	104 mm

Photometric data




Spectral Power Distribution Colour



Light Distribution Diagram


MASTER Glass LED bulbs

Photometric data


Colada-Rubio et al. • Polysaccharide and Polysaccharide-Protein Complexes
J. Neurosci., September 24, 2008 • 28(39):9775–9785 • 9785

General uniform lighting

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram

