

ToLEDo Vintage CANDLE

TOLEDO™ VINTAGE CANDLE 125LM E14 SL

0028010



Product features

- New and innovative Flexible Filament Chip Technology (FFCT) designed to create the low-lit vintage effect.
- Perfect for hotels, restaurants, heritage lighting, bars and decorative applications.
- The ideal LED solution to replace incandescent vintage candle lamp.
- Low glare – suitable for low height installation.
- 2000K colour temperature, to create a cosy ambience.
- Golden tinted glass envelope.
- 15,000 hours average rated life. Last 7.5 times longer than incandescent vintage lamps.
- Unique filament construction design – 'Cord' shape.
- Omni-directional light distribution – 300°.
- Low-lumen output to create low-lit effect – 125lm.
- More than 100,000X switching cycles.
- 3 years warranty.
- Environment friendly – no mercury and lower CO2 emissions.

PRODUCT OVERVIEW

Product code	0028010
Product name	TOLEDO™ VINTAGE CANDLE 125LM E14 SL
Technology	LED
Watt (Rated) (W)	2.3
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer,
Certifications	EUTIE103
ETIM Class	EC001959
Luminous flux (lm)	125
Colour temperature (K)	2000
Light colour	Candlelight 820
CRI (Ra)	80
Wattage (W)	2.3
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288280103

DATA TABLE

General data

Product code	0028010
Product name	TOLEDO™ VINTAGE CANDLE 125LM E14 SL
Technology	LED
Watt (Rated) (W)	2.3
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer,
Operating Temperature Range (°C)	25

ToLEDo Vintage CANDLE

TOLEDO™ VINTAGE CANDLE 125LM E14 SL

0028010

Certifications	EUTIE103
ETIM Class	EC001959

Optical data

Luminous flux (lm)	125
Luminous flux (Rated) (lm)	125
Colour temperature (K)	2000
Light colour	Candlelight 820
CRI (Ra)	80
Beam angle (Rated) (°)	360

Electrical data

Wattage (W)	2.3
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	50Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	97
Nominal Product Diameter (mm)	35
Weight (kg)	0.095

Packaging

Single packaging type	Carton
Product EAN number	5410288280103
Packaging single length (cm)	3.9
Packaging single width (cm)	3.9
Packaging single height (cm)	11.0
DUN14 (inner)	25410288280107
Units per inner package	6
Packaging inner length (cm)	12.0
Packaging inner width (cm)	8.5

ToLEDo Vintage CANDLE

TOLEDO™ VINTAGE CANDLE 125LM E14 SL

0028010


Packaging inner height (cm)	12.5
DUN14 (outer)	15410288280100
Units per outer package	60
Packaging outer length (cm)	45.5
Packaging outer width (cm)	26.6
Packaging outer height (cm)	14.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes

PHOTOMETRY

TECHNICAL DRAWINGS



ToLEDo Vintage CANDLE

TOLEDO™ VINTAGE CANDLE 125LM E14 SL

0028010

