

ToLEDo Radiance White 142mm

TOLEDO RADIANCE WH DIM 806LM 840 E27 SL

0029002



Product features

- Stylish and innovative solution • Fluid design - easily blend with the ambience and change the look and feel of the room • Uniform light distribution with an element of direct/indirect lighting • Dimmable functionality to set the desired light level • Low glare - suitable for low height installation • Construction: white housing, textured circular reflector and matt diffuser ring • E27 lamp base, easy-to-install • 25,000 hours average rated life • Lumen output: 806lm • High lumen efficacy - up to 101 lm/W • Product dimensions (WxL) : 142mm x 118mm • 3 years warranty • Environment-friendly - no mercury and lower CO2 emissions • CRI 80



PRODUCT OVERVIEW

Technology	LED
Ordering number	0029002
ETIM Class	EC001959
Luminous flux (lm)	806
Colour temperature (K)	4000
Light colour	4000 Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Wattage (W)	8
Product Voltage (V)	230
Average life (Nominal) (h)	25000
Product EAN number	5410288290027
Product Visible for Web	Y

DATA TABLE

General data

Technology	LED
Ordering number	0029002
E-number Sweden	8293672
E-number Finland	4740625
Notes	Dimmable

Tender text

Product name	TOLEDO RADIANCE WH DIM 806LM 840 E27 SL
Fixture rating	Open

• Stylish and innovative solution • Fluid design - easily blend with the ambience and change the look and feel of the room • Uniform light distribution with an element of direct/indirect lighting • Dimmable functionality to set the desired light level • Low glare - suitable for low height installation • Construction: white housing, textured circular reflector and matt diffuser ring • E27 lamp base, easy-to-install • 25,000 hours average rated life • Lumen output: 806lm • High lumen efficacy - up to 101 lm/W • Product dimensions (WxL) : 142mm x 118mm • 3 years warranty • Environment-friendly - no mercury and lower CO2 emissions • CRI 80

ToLEDo Radiance White 142mm

TOLEDO RADIANCE WH DIM 806LM 840 E27 SL

0029002

General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries,
Sales pack quantity	2
Operating Temperature Range (°C)	25
ETIM Class	EC001959

Optical data

No. of switching cycles before premature failure (min)	50000
Certifications	EUTIE103
Luminous flux (lm)	806
Luminous flux (Rated) (lm)	806
Colour temperature (K)	4000
Light colour	4000 Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam angle (Rated) (°)	360
Lumen maintenance at end of nominal life (%)	70

Electrical data

Watt (Rated) (W)	8
Wattage (W)	8
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<1
Product Voltage (V)	230
Lamp power factor	0.9
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	8
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

Single package volume (dm3)	3.564
Single product gross weight (kg)	0.289
Single packaging weight (kg)	0.155
Outer package net weight (kg)	0.268
Outer package gross weight (kg)	0.75
Outer package volume (dm3)	8.721
Outer packaging weight (kg)	0.482
Nominal Product Length (mm)	118
Nominal Product Diameter (mm)	142
Weight (kg)	0.134

ToLEDo Radiance White 142mm

TOLEDO RADIANCE WH DIM 806LM 840 E27 SL

0029002

Packaging

Single packaging type	Carton
Product EAN number	5410288290027
Packaging single length (cm)	16.0
Packaging single width (cm)	13.5
Packaging single height (cm)	16.5
DUN14 (outer)	15410288290024
Units per outer package	2
Packaging outer length (cm)	28.5
Packaging outer width (cm)	17.0
Packaging outer height (cm)	18.0

Safety data

Breakage cleaning instructions	Not Applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers
Safety message	Not Suitable for totally enclosed fixtures

ToLEDo Radiance White 142mm

TOLEDO RADIANCE WH DIM 806LM 840 E27 SL

0029002

