

ToLEDO Mirage G120

TOLEDO MIRAGE G120
0029908



Product features

- A perfect choice for hospitality, decorative and mood lighting applications Unique and innovative lamp design and construction Low-lumen output to create the low-lit effect and gives no glare Low power construction: only 2.5W Perfect for SylPendant fixtures - a range of unique and elegant E27 lamp pendants, available in copper, brass, black and white finish Candlelight 2000K colour temperature creates a warm and cosy ambience High colour rendering - CRI80 High quality, scratch and temperature resistant golden tinted glass envelope 25,000 hours of average rated life. Last 25 times longer than incandescent lamps Omni-directional light distribution of 300° Non-dimmable More than 100,000X switching cycles 3 years warranty



NOTES

undefined

PRODUCT OVERVIEW

| | |
|----------------------------|------------------------|
| IPC Code | 0029908 |
| Product name | TOLEDO MIRAGE G120 |
| Technology | LED |
| Watt (Rated) (W) | 2.5 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Residential & Consumer |
| Certifications | EUTIE103 |
| ETIM Class | EC001959 |
| E-number FI | 4740678 |
| Luminous flux (lm) | 125 |
| Colour temperature (K) | 2000 |
| Light colour | Candlelight |
| CRI (Ra) | 80 |
| Wattage (W) | 2.5 |
| Product Voltage (V) | 230 |
| Average life (Nominal) (h) | 25000 |
| Product EAN number | 5410288299082 |

DATA TABLE

General data

| | |
|---------------------|------------------------|
| IPC Code | 0029908 |
| Product name | TOLEDO MIRAGE G120 |
| Technology | LED |
| Watt (Rated) (W) | 2.5 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Residential & Consumer |

ToLEDO Mirage G120

TOLEDO MIRAGE G120
0029908

| | |
|----------------------------------|----------|
| Operating Temperature Range (°C) | 25 |
| Certifications | EUTIE103 |
| ETIM Class | EC001959 |
| E-number FI | 4740678 |

Optical data

| | |
|----------------------------|-------------|
| Luminous flux (lm) | 125 |
| Luminous flux (Rated) (lm) | 125 |
| Colour temperature (K) | 2000 |
| Light colour | Candlelight |
| CRI (Ra) | 80 |
| Beam angle (Rated) (°) | 100 |

Electrical data

| | |
|---|---------|
| Wattage (W) | 2.5 |
| Starting time (max) (s) | 0.5 |
| Warm-up time to 60% of full light (max) (s) | 1 |
| Product Voltage (V) | 230 |
| Lamp power factor | 0.5 |
| No. Of switching cycles before premature failures | 100000 |
| Lamp Energy Label (class) | A+ |
| kWh per 1000 hours burning time | 3 |
| Nominal Frequency (Hz) | 50/60Hz |

Lifetime data

| | |
|----------------------------|-------|
| Average life (Nominal) (h) | 25000 |
| Average life (Rated) (h) | 25000 |

Physical data

| | |
|-------------------------------|------|
| Nominal Product Length (mm) | 165 |
| Nominal Product Diameter (mm) | 125 |
| Weight (kg) | 0.14 |

Packaging

| | |
|---------------------------------------|----------------|
| Single packaging type | Carton |
| Product EAN number | 5410288299082 |
| Packaging single length / height (cm) | 17.8 |
| Packaging single width (cm) | 13.2 |
| Packaging single depth (cm) | 13.2 |
| DUN14 (outer) | 15410288299089 |
| Units per outer package | 4 |
| Packaging outer length / height (cm) | 28.0 |
| Packaging outer width (cm) | 28.0 |
| Packaging outer depth (cm) | 20.5 |

Safety data

| | |
|--------------------------------|----------------|
| Breakage cleaning instructions | Not applicable |
|--------------------------------|----------------|

ToLEDO Mirage G120

TOLEDO MIRAGE G120
0029908

| | |
|-------------------------------------|--|
| Special purpose lamp | No |
| Dry applications use only | Yes |
| Suitable for household illumination | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |

