

RefLED R80

REFLED R80 V3 806LM 830 E27 SL

0028413



Product features

- Energy efficient LED alternative for traditional incandescent and halogen blown reflector lamp
- Modern construction and attractive design
- Mercury free solution
- Long average rated lifetime: 15,000 hours
- Lower maintenance cost compared to traditional lamps
- Non-dimmable
- 3 years warranty
- Perfect for general lighting applications: residential lighting, down lights, hotels, hotels, restaurants, bars, lobbies, corridors, halls, etc



PRODUCT OVERVIEW

IPC Code	0028413
Product name	REFLED R80 V3 806LM 830 E27 SL
Technology	LED
Watt (Rated) (W)	9
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE105
ETIM Class	EC001959
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Wattage (W)	9
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288284132

DATA TABLE

General data

IPC Code	0028413
Product name	REFLED R80 V3 806LM 830 E27 SL
Technology	LED
Watt (Rated) (W)	9
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature rated (°C)	25

RefLED R80

REFLED R80 V3 806LM 830 E27 SL

0028413

Certifications	EUTIE105
ETIM Class	EC001959

Optical data

Rated Luminous Flux Useful (lm)	806
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Beam angle (Rated) (°)	120

Electrical data

Wattage (W)	9
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	2
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Dimmable	No
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	9
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	114
Nominal Product Diameter (mm)	81
Weight (kg)	0.15

Packaging

Single packaging type	Carton
Product EAN number	5410288284132
Packaging single length / height (cm)	4.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	7.8
DUN14 (outer)	15410288284139
Units per outer package	6
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	17.0
Packaging outer depth (cm)	12.5

RefLED R80

REFLED R80 V3 806LM 830 E27 SL

0028413

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

