

RefLED PAR38

RefLED RETRO PAR38 DIM 1200LM 830 IP65 40°S

0028271



Product features

- High performance LED PAR lamps with the same look and feel of traditional PAR lamps
- Glass construction - means no colours clashing between the lamp and fixture
- Reduced visible heatsink from the front
- Mercury-free solution
- Lower maintenance cost
- RefLED™ RT PAR38 IP65 is also suitable for outdoor applications when used with IP65 rated luminaires.
- Lifetime: up to 25,000 hours
- High lumen efficacy
- Dimmable on approved dimmers*
- 3 year warranty
- Suitable for general lighting and accent lighting for hotels, restaurants, bars, lobbies, corridors and halls



PRODUCT OVERVIEW

IPC Code	0028271
Product name	RefLED RETRO PAR38 DIM 1200LM 830 IP65 40°S
Technology	LED
Watt (Rated) (W)	15
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
Certifications	EUTIE105
ETIM Class	EC001959
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	40
Wattage (W)	15
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288282718

DATA TABLE

General data

IPC Code	0028271
Product name	RefLED RETRO PAR38 DIM 1200LM 830 IP65 40°S
Technology	LED
Watt (Rated) (W)	15
Cap/Base	E27

RefLED PAR38

RefLED RETRO PAR38 DIM 1200LM 830 IP65 40°S

0028271

Fixture rating	Open
General application	Hospitality,Museums & Galleries,Residential & Consumer,Retail
Operating temperature rated (°C)	25
Certifications	EUTIE105
ETIM Class	EC001959

Optical data

Rated Luminous Flux Useful (lm)	1200
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	40
Beam angle (Rated) (°)	40

Electrical data

Wattage (W)	15
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<0.5
Product Voltage (V)	230
Lamp power factor	0.9
No. Of switching cycles before premature failures	50000
Dimmable	Yes
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	15
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

Nominal Product Length (mm)	134
Nominal Product Diameter (mm)	121
Weight (kg)	0.405

Packaging

Single packaging type	Carton
Product EAN number	5410288282718
Packaging single length / height (cm)	15.1
Packaging single width (cm)	13.2
Packaging single depth (cm)	13.2
DUN14 (outer)	15410288282715
Units per outer package	6
Packaging outer length / height (cm)	43.7
Packaging outer width (cm)	29.6

RefLED PAR38

RefLED RETRO PAR38 DIM 1200LM 830 IP65 40°S
0028271

Packaging outer depth (cm) 21.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	General lighting
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers

